

RESISTENCIAS TUBULARES FLEXIBLES

		Diámetro 8 mm	Diámetro 8.5 mm
Longitud	Longitud caliente	wattage	Wattage
300 mm	240 mm	560	650
350 mm	290 mm	675	750
400 mm	340 mm	795	900
450 mm	390 mm	910	1050
500 mm	440 mm	1025	1150
550 mm	490 mm	1145	1300
600 mm	540 mm	1260	1450
650 mm	590 mm	1380	1600
700 mm	640 mm	1495	1750
750 mm	690 mm	1615	1900
800 mm	740 mm	1730	2050
850 mm	790 mm	1845	2200
900 mm	840 mm	1960	2350
950 mm	890 mm	2080	2500
1000 mm	940 mm	2195	2650
1050 mm	990 mm	2316	2800
1100 mm	1040 mm	2430	2930
1150 mm	1090 mm	2545	3060
1200 mm	1140 mm	2665	3190
1250 mm	1190 mm	2780	3320
1300 mm	1240 mm	2895	3450
1350 mm	1290 mm	3015	3580
1400 mm	1340 mm	3130	3600
1450 mm	1390 mm	3245	3600
1500 mm	1440 mm	3365	3600
1550 mm	1490 mm	3480	3600
1600 mm	1540 mm	3600	3600
1650 mm	1590 mm	3600	3600
1700 mm	1640 mm	3600	3600
1750 mm	1690 mm	3600	3600
1800 mm	1740 mm	3600	
1850 mm	1790 mm	3600	
1900 mm	1840 mm	3600	
1950 mm	1890 mm	3600	
2000 mm	1940 mm	3600	
2050 mm	1990 mm	3600	
2100 mm	2040 mm	3600	



Resistencia de 8.0mm: ranura diámetro 8.0mm (resistencia 8.2mm) radio min. 10mm, tolerancia de la ranura 7.95 +/- 0.1

Resistencia de 8.5mm: ranura diámetro 8.5mm (resistencia 8.7mm) radio min. 10mm, tolerancia de la ranura 8.45 +/- 0.1

Resistencia de 6.5mm en diámetro sobre pedido.